

SBTL322

Swing Barrier Turnstile for
Additional Lane

RFID and fingerprint



The SBTL322 is a swing barrier turnstile for additional lane series designed for smooth and silent operation and draws very little power. It's made of stainless steel which makes SBTL322 highly durable.

SBTL322 barriers are normally held in a locked position, thus denying access to the secured side. Upon SBTL322's reader (RFID and/or fingerprint) positively recognizing a user's valid access card or fingerprint, its barriers swing automatically, thus allowing users passage to the secured side.

During power outage, the user can push through the barrier easily to exit to safety. SBTL322 provides both security and convenient space, all in a very durable and elegant compact design.

Features

Reliability

- SUS304 stainless steel casework ensure long-lasting durability.
- High quality electrical components.

Safety Features

- Barriers unlock automatically during power outage.
- All smooth finish. No exposed screws.
- Ergonomic design makes card and fingerprint authentication fast & simple for users.

Built-in Reader Integration

- SBTL322 series ships already integrated with our customers' preference for either card or fingerprint access control reader. This greatly reduces installation time & expense.
- SBTL322 series and associated access control readers are all factory-tested prior to shipping.
- ZKTeco provides true plug & play turnstiles with the lowest possible total cost of ownership in the industry.

Simplification

- Simplify structure and connection, easy to maintain.
- LCD display screen shows the current running status, easy operation.

Specifications

| | |
|--------------------------|----------------------------------|
| Power Requirements | AC110V/220V, 50/60HZ |
| Working Temperature | -20°C ~ 70°C |
| Working Humidity | 5% ~ 95% |
| Infrared Sensor | 4 pairs |
| Working Environment | Indoor/Outdoor (if shelter) |
| Max. Speed of Throughput | 30 people per minute |
| Lane Width (mm) | 750 |
| Dimensions (L*W*H) | 1200 * 200 * 980 (mm) |
| LED Indicator | Support |
| Cabinet Material | SUS304 Stainless Steel |
| Lid Material | SUS304 Stainless Steel + Acrylic |
| Barrier Material | Acrylic |
| Barrier Movement | Swing |
| Emergency Mode | Support |
| Security Level | Medium |
| MCBF | 2 million |
| Opening Time | 0.8s |
| Opening Noise | ≤30dB |

