



F 18
Standalone Fingerprint Reader Controller

# Modern standalone fingerprint controller with color display



#### Biometric Performance:

Reliable, durable and highly accurate ZK fingerprint sensor with latest fingerprint matching algorithm which provides less than 1.5 second user recognition.



#### Communication:

Weigand output for connecting to access control panel and Ethernet port for fast and reliable communication with the computer



## Easy Operation and Management:

Works without computer. Complete setup and programming can be done via keypads and embedded firmware. Audio-Visual Indication for acceptance and rejection of valid/invalid fingerprints, cards and passwords.



#### Options:

Internal Proximity Card or Mifare Card reader allows dual factor authentication for access control.



#### Full Access Control Built In:

Relay Outputs for electric lock and alarm. Inputs fordoor status sensor and request to exit hardware. Supports multipletimezones and personnel groups for programming valid entry zones.



## Capacity:


Can store up to 3,000 templates and 30,000 transactions. The data can be backed up to a USB flash drive and can also be transferred to another reader in the absence of computer connectivity.




# For Software Developers:

Free SDK and development tools are available for developers/partners who wish to integrate F18 with any application which requires verifying people. Custom development is also available for OEM partners upon request.

# Standalone Installation



# Installation with Access Control Panel



# Specifications

#### Capacity

Fingerprint: 3,000 templates Transactions: 30,000

#### Display

3.5in TFT LCD Color Display

#### Communication

Ethernet, Weigand Input and Output,

RS485, USB Host

### Access Control Interface

3rd party electric lock, Door sensor, Exit button, Alarm, Door bell

# Power

12V DC, 3A

#### Environment

Operating Temperature: 32° to 113° F (0° to 45° C)

Operating Humidity: 20% to 80%

## Supported Options

ID Card, Mifare Card

#### **Dimensions**

Height: 7.20in (18.3cm) Length: 3.15in (8.0 cm) Width: 1.65in (4.2 cm) Weight: 0.90lbs (0.41kg)

# Part Numbers

F18

F18-ID with Proximity card reader

F18-HID with HID card reader

F18-M with Mifare card reader

# What's in the Box













Design and Specifications subject to change without notice

6 Kingsbridge Road, Suite 8 Fairfield, NJ 07004

+1 862 505 2101

sales@zkaccess.com

zkaccess.com

