

ZKBio830

All-in-One Biometric Smart POS Terminal



Features

- Power-efficient Intel®Core i5 4200U (1.6 GHz)
- Slim stand design with small footprint
- Multiple I/O interfaces for peripherals
- Standard with 4G Ram – HDD 500Gb SATA
- Optional built in 1D/2D barcode scanner, MSR, RFID
- Optional VFD & 15" & 10" customer display
- Faster installation and maintainability

Optional Accessories



RFID Card Reader



2nd LCD Display Screen



Barcode Scanner



Fingerprint Verification



Thermal Printer



Cash Drawer



VFD Customer Display

Specifications

System	
Processor	Intel® Celeron Intel Core i5 4200U(1.6 GHz)
System Memory	4GB Standard, DDR3L 1333MHz (Max.8GB)
Storage Device	HDD 500Gb SATA
OS Supported	Windows 7, Windows 8, Windows 10 IoT Enterprise, POS Ready 7, Linux
Audio	Realtek ALC662
Display and Touch	
Types	15" TFT LCD, LED Backlight
Resolution	1024*768
Touch Screen	Five-wire analog resistive or projected capacitive
Customer Display	LED (8C digital tube)
External I/O Ports	
VGA	1*DB-15
USB	5*USB2.0, 1*USB3.0
COM	5
LAN	1*RJ45
Audio	1*line-out
Cash Drawer	1
Power	
Power Supply	Adaptor 12V DC 5A
Physical Environmental	
Operating Temperature	0°C ~ 35°C at 20%-80% humidity
Storage Temperature	- 20°C ~ 55°C at 20%-80% humidity
Dimensions (L*W*H)	347*372*402mm
Packing Dimensions	450*420*480mm
Net Weight	6.10kg
Packing Weight	8.21kg
Certification	CE FCC
Options & Peripherals	
Second Display	10"&15" TFT LCD
Customer Display (VFD)	VFD (2*20 lines)
MSR	3 tracks
Fingerprint	Built-in fingerprint reader

