



VALKYRIE CS

Conventional Wall Mount Sounder/ Beacon

1328-CPR-0287
CERTIFIED

The VALKYRIE CS is a wall mounted Conventional Sounder/ Beacon with low power consumption. Four different tones are available and selected using DIL switches 1 and 2.

Both continuous and pulsing outputs are provided via separate negative supply connections allowing for the presence of differentiated evacuation and alert sounds.

TECHNICAL SPECIFICATIONS	
SUPPLY VOLTAGE	20 V to 30 V DC
CURRENT - SOUNDER/ BEACON ACTIVE	10 mA - 280 mW @ 28 V DC
SOUNDER OUTPUT	97.5 dB (@ 1 meter - 30 V DC)
CABLE SIZE	0.5-2.5 mm ²
RESET/START-UP TIMES	20 seconds max.
OPERATING TEMPERATURE	-10°C to 55°C
MAX. HUMIDITY	95% RH Non-Condensing
CASE MATERIAL	ABS & PC - Flame Retardant rating UL 94 V2
COLOUR	White or Red
PROTECTION	Type A - Indoor Use IP21C
DIMENSIONS	110 (D) x 85 (H) mm inc. base
WEIGHT	254 g - inc. base

ORDER CODE		
VALKYRIE CS-WHITE	1328-CPR-0287	CONVENTIONAL WALL SOUNDER - WHITE
VALKYRIE CS-RED	1328-CPR-0287	CONVENTIONAL WALL SOUNDER - RED
VALKYRIE CSB-WHITE	1328-CPR-0287	CONVENTIONAL WALL SOUNDER/ BEACON - WHITE
VALKYRIE CSB-RED	1328-CPR-0287	CONVENTIONAL WALL SOUNDER/ BEACON - RED